

METHODOLOGY FOR APPLICATION OF MYK COAT PUD

Description:

MYK Coat PUD is two component water based Polyurethane resin dispersion specially formulated to provide durable, UV resistance and breathable system for interior and exterior coating for both concrete walls and floors etc. It is hygienic, gives aesthetic finish, excellent adhesion and good chemical resistance.

Packing: 6 Kg Pack

Methodology for Application:

Step-1:- Mixing of **MYK Coat PUD**

Step-2:- Application of **MYK Coat PUD**

Primer:-

Optional: - Depending on surface condition Primer will be recommended. Please contact Technical cell of **MYK Schomburg** for recommendation.

Mixing of MYK Coat PUD:

Stir the Hardener and Resin individually with drill mixer of proper size. Then add the entire content of the hardener into Resin container and stir the two components thoroughly using a low speed mixer for about 2 to 3 Minutes until a uniform color of the mixture is obtained.

Application of MYK Coat PUD:

The mixed material is to be applied to the dry and prepared surface by using paint brush or good quality of lambswool roller or spray equipment.

Application Areas:

Concrete wall and floors, precast concrete slab/ panels; cement based plaster, Balconies, terrace, show room, Operation Theater, Industrial areas, Hygienic rooms, outdoor exterior coating etc.

Coverage:

4m² per kg @ 80 microns thick.

Protection:

MYK Coat PUD should be applied with gloves and care should be taken to see that it doesn't fall on screen or eyes. Splashes on the eyes have to be immediately washed with plenty of water and medical advice to be taken.

Note: - All coverages mentioned above are theoretical and under laboratory conditions, MYK Schomburg strongly recommends actual site trials to ascertain actual coverages.