

## METHODOLOGY FOR APPLICATION OF MYK DS25 ACRYLIC

### Description:

**MYK DS25 Acrylic** is a single compound, ready to use, transparent, acrylic sealer for porous walls and floors. It penetrates and seal the pores of the concrete and also increases abrasion resistance, reduces absorption and provides an easy to clean, dust free finish.

**Packing:** 1, 10 and 25 Kg pack

### Methodology for Application:

**Step-1:-** Mixing of **MYK DS25 Acrylic**

**Step-1:-** Application of **MYK DS25 Acrylic**

### Mixing of MYK DS25 Acrylic:

Mix the material with a mechanical stirrer for 2 minutes before doing the application.

### Application of MYK DS25 Acrylic:

A two coat application is necessary. For extremely dry and porous surfaces it is recommended that the first coat be diluted at a 1:1 ratio by volume. The diluted material mixed thoroughly and applied by brush to a desired thickness. Squeegee or roller can be used depending on applicators.

Once it is coated, the surface should be protected against moisture condensation. Water and dust for at least 6 hours.

### Application Areas:

It is used to seal walls, floors and ceiling against dusting. It is also used as curing membrane as it significantly reduces water evaporation when applied to fresh (green) concrete surfaces.

### Coverage:

2.5-3.3 m<sup>2</sup> per kg in two applications.

### Protection:

**MYK DS25 Acrylic** should be applied with gloves and care should be taken to see that it doesn't fall on screen or eyes. Splashes on the eyes have to be immediately washed with plenty of water and medical advice to be taken.

**Note:** - All coverages mentioned above are theoretical and under laboratory conditions, MYK Schomburg strongly recommends actual site trials to ascertain actual coverages.