

METHODOLOGY FOR APPLICATION OF MYK INDUFLOOR EC

Description:

MYK Indufloor EC is basically a three component solvent free epoxy resin system, which is available in various colors and it can be applied in various thickness. It is dust free easily cleanable seamless and hygienic in nature.

Packing: 5 Kg Pack

Step-1:- Priming the Surface with a suitable primer

Step-2:- Mixing of **MYK Indufloor EC**

Step-3:- Application of **MYK Indufloor EC**

Primer should be applied before doing the application of Coating.

Mixing of MYK Indufloor EC:

The preweighed packs of the three components resin, hardener and colour paste have to be mixed individually for 3 to 4 minutes with slow speed drilling machine. The colour paste should be added to the base and stirred for 30 seconds. Then add the hardener content to the base until an even colour and texture is obtained.

Application of MYK Indufloor EC:

The first coat is applied by brush and the second is applied by sponge roller after the first coat is completely dried. The total application is carried out when the primer is completely dried.

Coverage:

3 m² per 1kg @ 200 microns thick.

Application Areas:

Dairies and Soft drink production unit, laboratories, computer assembly unit, chemical manufacturing unit, car parking areas.

Protection:

MYK Indufloor EC should be applied with gloves and care should be taken to see that it doesn't fall on screen or eyes. Splashes on the eyes have to be immediately washed with plenty of water and medical advice to be taken.

Note: - All coverages mentioned above are theoretical and under laboratory conditions, MYK Schomburg strongly recommends actual site trials to ascertain actual coverages.